




REICHWALD + Co

Lieferprogramm

Geschweißte

Gewinderohre


Gewinderohre EN 10255 (DIN 2440)



Schwarz

Durchmesser			Wanddicke s in mm	Gewicht kg / m
Zoll	DN	d in mm		
1/8	6	10,2	2,00	0,407
1/4	8	13,5	2,35	0,650
3/8	10	17,2	2,35	0,852
1/2	15	21,3	2,65	1,22
3/4	20	26,9	2,65	1,58
1	25	33,7	3,25	2,44
1 1/4	32	42,4	3,25	3,14
1 1/2	40	48,3	3,25	3,61
2	50	60,3	3,65	5,10
2 1/2	65	76,1	3,65	6,51
3	80	88,9	4,05	8,47
4	100	114,3	4,50	12,10
5	125	139,7	4,85	16,20
6	150	165,1	4,85	19,20

Gewinderohre EN 10255 (DIN 2440)



Verzinkt

Durchmesser			Wanddicke s in mm	Gewicht kg / m
Zoll	DN	d in mm		
1/8	6	10,2	2,00	---
1/4	8	13,5	2,35	0,68
3/8	10	17,2	2,35	0,89
1/2	15	21,3	2,65	1,27
3/4	20	26,9	2,65	1,65
1	25	33,7	3,25	2,55
1 1/4	32	42,4	3,25	3,28
1 1/2	40	48,3	3,25	3,77
2	50	60,3	3,65	5,33
2 1/2	65	76,1	3,65	6,80
3	80	88,9	4,05	8,85
4	100	114,3	4,50	12,60
5	125	139,7	4,85	16,80
6	150	165,1	4,85	20,00